



ProLube® Bio Multipurpose Lithium EP Grease **Biodegradable Lubricating Grease on a lithium basis**

ProLube® Bio Multipurpose Lithium EP Grease is a premium quality grease that is biodegradable, water washout resistant, formulated mostly with the best European crop oils and lithium based thickener and extreme pressure additives for extreme performance.

ProLube® Bio Multipurpose Lithium EP Grease meets OECD 301 tests for biodegradability, the USDA content criteria for Biobased labels and is non-bioaccumulative, not toxic to plants, and aquatically non-toxic. Note: the user of all ProLube® products is responsible for ensuring the use of these products meets the local laws and ordinances.

ProLube® Bio Multipurpose Lithium EP Grease includes additives to minimize friction and wear. It delivers High Film Strength common in vegetable oils and offers superior lubricity and high-temperature stability. The Bio Multipurpose Lithium EP Grease Grease is made from base oils that offer Higher flash point than petroleum oils for increased safety; and excellent oxidation stability. It meets the USDA's proposed Biobased content requirement for the Biopreferred/Biobased labeling. The Bio Multipurpose Lithium EP Grease uses base oils made from crop oils like rapeseed oils that offer higher oxidation stability and low temperature flowability.

ProLube® Bio Multipurpose Lithium EP Grease is suitable for the demanding automotive and industrial application. It can be used in a wide range of operating temperatures and the high flashpoint lowers fire hazards, thereby making usage safer. It finds a wide range of usages in light and heavy industries, construction equipment, roadwork machines, mining equipment, ships, as well as passenger cars and trucks. Ideal for: bearings, articulated joints, transmissions, slides, shafts, rollers, cog wheels, water pumps, truck fifth wheel, vehicle chassis and many others. ProLube® Bio Multipurpose Lithium EP Grease is designed for highest severity applications as well as being suitable for environmentally sensitive areas.

Representative Technical Data:

NLGI Grade	2
Appearance	Ivory
Cone Penetration, Worked 60 Strokes	265-285
Four Ball Wear Scar (mm)	0.47
Four Ball Weld Load (kg)	500
Dropping Point (°C)	+195
Water Resistance @80°C (% Loss)	11.6%
Base Oil Viscosity at 40°C (cSt)	90
Base Oil Viscosity at 100°C (cSt)	16
Base Oil Viscosity Index	191
Base Oil Flash Point, °C	+329
Operating temperature range, °C	-42 to +145
Base Oil Biodegradability OECD 301F	Pass
Base Oil Aquatic Toxicity OECD 202	Non-toxic, Pass

Packaging: Please contact ProLube®

Note to Users: THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, PROLUBE® MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, PROLUBE® RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.

